



BUTYL GLYCOL INDUSTRIAL GRADE

Notes: Product analysis as reported by an independent third-party surveyor.

Re-testing is recommended 12 months from the date of the original COA to verify product quality.

For SINO TRAC FZE

Disclaimers Because of the nature of manufacturing processes, our products do not contain any plant or animal products. It is the responsibility of our customers to determine that their use of our product (s) is safe, lawful and technically suitable in their intended applications. Because of possible changes in law and regulations, as well as possible changes in our products, we can not guarantee that the status of this product will remain unchanged. We, therefore, recommend that customers continuing to use our products verify their status regularly.

Sales Specification

TEST	METHOD	UNITS	SPECIFICATION	RESULTS
Appearance	Visual	-	Clear, Clean liquid	Clear, Clean liquid
Colour	ASTM D 1209	Pt/Co	10 max	LT 5
Density @ 20°C in Vac	ASTM D 4052	kg/L	Report	0.9002
Specific Gravity @ 20/20 °C	ASTM D 4052	-	0.901-0.903	0.9018
Acidity as Acetic Acid	ASTM D 1613	% wt	0.01 max	0.004
Water Content	ASTM E 203	% wt	0.10 max	0.02
Purity	GC	% wt	99.4 min	99.8
Distillation			-	-
IBP	ASTM D 1078	°C	169 min	169.0
DP			172.5 max	172.0